

## Strong and reliable, safety with a lot of comfort

With ICS you boost the convenience of your system, can rely on planing and investment security as well as the durability and long service life of the system. ICS is a stable reversible key system that is so powerful that sufficient locking system reserves can be taken into account during the planning stage. ICS is ideal for locking systems with complex structures, e.g. in office buildings, schools or student residences.

ICS offers different locking technologies for high protection: the proven curve system, the durable length profile and the distinctive track system with internal recesses.

The ICS key has increased copy protection and can hardly be copied even with modern 3-D printing processes.

## Measurements

- clamping dimension (H7233): 27,2 mm
- installation depth: 32,2 mm
- mounting hole: Ø 22,5 mm lateral reduced to 18 mm
- cylinder front: Ø 24,8 mm

## Technical characteristics

- the scanning takes place in five tracks through 13 spring-loaded locking elements and the durable length profile
- 2 lateral pin rows with 10 undivided locking pins scan the curves on the key sides
- 1 central row of pins with 3 track pins checks the internal, concealed recesses on the narrow sides of the key
- combination of divided and undivided locking elements
- querying the locking authorisation on the key in four levels
- locking authorisation check at up to 15 key positions and one reversible key profile
- drilling protection: hardened HSS steel pins in the cylinder core
- picking and scanning protection through specially shaped locking pins
- impact key protection
- locking path: 90°, lever adjustable in 45° steps by 360 degrees
- secured against rotation by two surfaces
- for material thickness up to 17 mm
- with thread M22 for fixing nut SW27
- patent protection until 2029

## Execution

- reversible key system with vertical key insertion
- locking by closing lever
- key can only be removed when closed
- base material: brass
- locking lever: galvanised steel
- drive plate, fixing screws: galvanized steel
- combination with electronic locking system possible

## Options / Special equipment




- different closing lever variants (standard closing lever H7233: 33 mm)

## Operational area

- wood and metal doors
- mailboxes, key boxes
- emergency key boxes, showcase locks
- cloakroom boxes/lockers
- office building, hotels & service stations, residences
- schools, libraries, associations
- student residences and nursing homes


## Scope of delivery

- camlock cylinder / lever cylinder MB23 incl. 2 or more keys
- selected closing lever, mounted
- fixing nut M22
- Security card




## Key

- key thickness: 3 mm
- reversible key made of special resistant nickel silver alloy
- patented concealed curve guidance and optimized curve on the key
- easy key insertion through specially developed key chamfers
- three equally long incisions on the back of the key do not allow any conclusions to be drawn about the depth of the incisions, making illegal key production virtually impossible, even with the latest 3D printing processes
- high security against decryption
- very resistant, low-wear
- high comfort through functional, rounded form
- optional: ergonomic design key \*, key with coloured dot \*, key with extended key neck \*




### Key with design cap

- colours: black, blue and red, yellow, green and white
- material thickness design cap: 7,2 mm
- plastic caps for special design requirements for the keys
- ergonomic design and high quality for better haptics
- easy optical differentiation
- simple management of locking systems through colour assignment
- consecutive numbering of the key (key with the same locking authorisation receives a consecutive number)
- use exclusively for EVVA keys
- **factory assembly, subsequent opening and retrofitting is not possible**




### Key with coloured dot

- colours: red, blue, green, yellow, brown, black, violet, pink
- with countersunk colour dot on the key neck
- for optical differentiation
- colour dot may differ from the image on the website



### Key with extended key neck

- specially shaped key
- for use with armoured fittings



## Technical details

The reversible key system ICS (Inside Code System) offers high protection thanks to the unique combination of three different locking technologies:

- the specially shaped, resistant length profile
- the tried-and-tested curve system that scans the locking authorisation
- The improved pin system: this consists of concealed, internal recesses on the ICS key body - this is unique worldwide! This makes unauthorised key copies almost impossible.
- Security card

The scanning takes place in five tracks through 13 spring-loaded locking elements and the durable length profile, thus ensuring a high level of safety.

### Locking cylinder security

The innovative technologies of the ICS cylinder offer sustainable protection against illegal opening methods:

- **Picking and scanning protection**



Divided and undivided query elements prevent the query positions from being detected. Opening the ICS cylinder with locking tools becomes practically impossible. The fictitious opening positions of the lateral system rows virtually exclude scanning of the ICS cylinder.

- **Drilling protection**

The chrome vanadium elements in the ICS cylinder protect it from destructive opening techniques. Additional security elements offer high resistance to attack.

- **Impact key protection**

With this complicated opening method, burglar professionals use a so-called impact key to try to bring the query positions in the cylinder into the correct position.



\* this selection extends the delivery time