# PRODUCT DATA SHEET





SKU IS.GERA.4510.KZ Producer No. 4510

ISEO GERA WS is a reversible key profile. The large number of profile variants in combination with 6 locking authorisation queries via the pin system offers a high degree of security against unauthorised re-locking. The nickel silver reversible keys are corrosion-free, low-wear, easy to handle and offer good locking convenience.

Key blanks of the profile series GERA WS are not freely available in the trade.

### **Basic length**

- from 30/30 mm
- · measured from the middle of cam
- · extension 5 mm per side
- · The knob is always located on the inside of the cylinder.

#### **Technical characteristics**

- · 6 pairs of locking elements
- · core pins made of special brass
- standard drilling protection (ABS/A): two hardened dowel pins each
  in the core and in the body, on one side and on the outside of the cylinder
- according to DIN 18252/DIN EN 1303 class P3 (cylinders are marked with quality mark and registration number)
- · with trademark protection

#### Execution

- · reversible key system
- · horizontal key insertion
- · cylinder body: matt nickel plated

### **Options / Special equipment**

· increased drilling protection

# Operational area

- front doors, connecting doors, office doors, interior doors, exterior doors, apartment doors, gates, wooden doors, aluminium doors, tubular frame doors, etc.
- · private houses and apartments
- · office and commercial areas

### Scope of delivery

- · knob cylinder (type 4510) incl. 3 or more keys
- 1 fixing screw M5
- · Security card

### **Drilling protection (ABS/A)**

- · two hardened dowel pins each in the core and in the body
- · on one side and on the outside of the cylinder

### Increased drilling protection (ABS/E)


• two hardened cylindrical pins in the core and one carbide pin in the core above the profile as well as two carbide pins in the body

Tel: +49 351 850 71 000

Fax: +49 351 413 92 595

- 1. and 2. pair of pins with hardened steel core or hardened steel
- · on one side and on the outside of the cylinder





## Key

- · key thicknes: 3 mm
- · reversible key made of nickel silver
- · corrosion-free, low-wear
- easy to handle and good closing comfort
- · no key blanks freely available on the market

