PRODUCT DATA SHEET



3VS camlock cylinder / lever cylinder 3650



SKU WI.3VS.BK.3650 Producer No. 3650

The 3VS system is the new Sinus reversible key profile.

SINUS - this is the name of the new system family from WILKA. The new keyways meet all the expectations put on cylinders in complex locking systems.

Measurements

- · installation depth: 43 mm
- · clamping dimension (lever 001): 31,5 mm
- mounting hole: Ø 27,7 mm lateral reduced to 24,3 mm

Technical characteristics

- 6 pin locking elements, class 80
- up to 12 profile control pins in two additional levels
- standard drilling protection (1 body pin and 1 core pin made of hardened steel)
- · 1 stylus pin made of hardened steel for drilling protection
- · special pins for picking resistance
- highest patented key copy protection due to additional protector pin on the key
- · locking path: 90°, lever adjustable in 45° steps by 360 degrees
- · patent protection until 2036

Execution

- · comfortable reversible key system
- · horizontal key insertion
- · cylinder body: brass matt nickel-plated
- steel closing lever
- · key can only be removed when closed (compulsory locking)
- easy integration into the "easy" electronic locking system through mechatronic key

Options / Special equipment

- · different cylinder finishes *
- different closing lever variants (standard closing lever 001: 21 x 3,5 x 38 mm)

Locking paths

- · locking path A: closed on the left, open on the top
- · locking path B: closed on the right, open on the top
- · locking path E: closed on the top, open on the left
- · locking path F: closed on the top, open on the right

Operational area


- · letter box systems, metal cabinets, cassettes, tool compartments, etc.
- · private houses and apartments
- · commercial sectors


Scope of delivery


- · camlock cylinder / lever cylinder 3650 incl. 1 or more keys
- brass hexagon fastening nut M28 x 1 mm (SW36)
- Security card












Key

Tel.: +49 351 850 71 000

Fax: +49 351 413 92 595

- key thickness: 3,55 mm
- paracentric key profile against unauthorized opening with locking tools
- protector nickel silver key made of high-quality, low-wear nickel silver (highest patented key copy protection)
- · reversible key
- new key design for use with standard security fittings



* this selection extends the delivery time