# PRODUCT DATA SHEET



## Carat S3 camlock cylinder / lever cylinder 3650



SKU WI.CaratS3.BK.1250 Producer No. 3650

The Carat S3 system is the new sinusoidal reversible key profile.

SINUS - that is the name of the new system family from WILKA. The new keyways fulfil all expectations that can be posed to a cylinder of a complex keying system.

#### Measurements

- · installation depth: 43 mm
- · clamping dimension (lever 001): 31,5 mm
- mounting hole: Ø 27,7 mm lateral reduced to 24,3 mm

#### **Technical characteristics**

- 6 pin locking elements, class 80
- up to 12 profile control pins in two additional levels
- standard drilling protection (1 body pin and 1 core pin made of hardened steel)
- 1 stylus pin made of hardened steel for drilling protection
- · special pins for picking resistance
- highest degree of copy protection due to protector pins on key and in cylinder core
- locking path: 90°, lever adjustable in 45° steps by 360 degrees
- patent protection until 2036

#### **Execution**

- · comfortable reversible key system
- · horizontal key insertion
- · cylinder body: brass matt nickel-plated
- steel closing lever
- · key can only be removed when closed (forced closure)
- easy integration into the "easy" electronic locking system through mechatronic key

### **Options / Special equipment**

- · different cylinder finishes \*
- different closing lever variants
  (standard closing lever 001: 21 x 3,5 x 38 mm)

# Locking paths


- · locking path A: closed on the left, open on the top
- · locking path B: closed on the right, open on the top
- · locking path E: closed on the top, open on the left
- · locking path F: closed on the top, open on the right

#### Operational area

- · letter box systems, metal cabinets, cassettes, tool compartments, etc.
- · private houses and apartments
- · commercial sectors

### Scope of delivery

- · camlock cylinder / lever cylinder 1250
- incl. 1 or more keys
- brass hexagon fastening nut M28 x 1 mm (SW36)
- · Security card




## Key

Tel.: +49 351 850 71 000

Fax: +49 351 413 92 595

- · key thickness: 3,55 mm
- paracentric key profile against unauthorized opening with locking tools
- protector nickel silver key made of high-quality, low-wear nickel silver (highest patented key copy protection)
- · reversible key
- · new key design for use with standard security fittings



\* this selection extends the delivery time