PRODUKTDATENBLATT



keyTec X-tra knob cylinder



SKU WINK.XTRA.KZ Producer No. X-tra 04

The system combines the advantages of conventional "serrated keys", such as a wide range of key profiles and a large number of variants, with the convenience of reversible key systems.

In addition to convenient operation, the variable locking surfaces with up to 20 spring-loaded radial pins and multiple stepped calotte bores, standard drilling and pulling protection and the special convex shape of the key ensure the high security of the X-tra reversible key system.

Basic length

- · from 30,2/30,2 mm
- · measured from the middle of cam
- · extension 5 mm per side
- · The knob is always located on the inside of the cylinder.

Technical characteristics

- · up to 20 radially arranged locking pins in 4 rows per side
- standard drilling and pulling protection: on the outside additional carbide pins in the cylinder core and in the cylinder body
- · picking protection
- · high manipulation protection
- · modular cylinder design for subsequent length change
- · reinforced key insertion through special cylinder cores
- · manufactured according to DIN 18252 and EN 1303
- patent protection until 2025

Execution

- reversible key system
- · comfortable vertical key insertion
- · cylinder body: nickel plated brass
- one-piece locking cam made of sintered steel, non-toxic corrosion protection
- · lockable from the outside with key, inside with knob
- oval knob, more handy and grippy
- the key can turn up to 355° empty to find the coupling
- combination with electronics possible (mechatronic key or mechanical key with integrated transponder for the operation of electronic components double knob cylinder, access reader, door fitting

Options / Special equipment

- · different cylinder finishes *
- drilling and pulling protection according to VdS **
- · key caps

Operational area

- front doors, connecting doors, office doors, interior doors, exterior doors, apartment doors, gates, etc.
- · interior and exterior areas, in connection with DIN mortise locks

Scope of delivery


- · knob cylinder incl. 3 or more keys
- · fixing screw
- · Security card














Key

- · key thickness: 3,4 mm
- · comfortable reversible key
- · increased wear resistance due to nickel silver material
- · ergonomically shaped key head for better grip
- 13,5 mm key shaft for the combination of all common safety fittings
- variable longitudinal profiles prevent the insertion of unauthorised keys
- · special key tip for better insertion comfort
- · key cap in different colours optionally available
- material thickness cap: 5,8 mm
- 5 intensive colours: blue, yellow, green, red, black

